

MWX211 PCB Spring Type Terminal Block, with Lever




Dimensions/Positions


		MWX211-508	MWX211-750
間距	Pitch	5.08mm	7.50mm
尺寸a	Dimension a	5.08mm	7.50mm
長度 A	Length	A= 5.08xP+1.50mm(P≥2)	A= 7.50xP +1.50mm(P≥2)
塑膠本體	Housing Material	PA 66	PA 66
彈片	Spring	Stainless Strip Steel	Stainless Strip Steel
端子	Contact	Brass, Tin Plated	Brass, Tin Plated
電線線徑	Wire Size	14 ~ 20AWG	14 ~ 20AWG
端蓋	Cover	PA 66	PA 66
PCB孔徑	PCB Hole Diameter	1.2mm	1.2mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

絕緣材料組	Insulating Material group	I	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	4 kV	6 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	4 kV	6 kV
額定電壓(III/3)	Rated voltage(III/3)	250V	400V
額定電壓(II/2)	Rated voltage(II/2)	630V	1000V
絕緣材料	Insulating Material	PA	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	300V	300V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	10A	16A



PCB Layout



PCB Layout